

MLA212 MLA series MLA212DA

Line Array System





The **MLA212** is a 2.5-way line array loudspeaker for long throw distance scale sound reinforcement, fitted with two 12" neodymium LF driver and two 1.4" neodymium HF driver, made of high quality plywood with polyurea waterproof paint. All rigging parts are made of aluminium alloy. The MLA212DA is equipped with FA2.38 digital amplifier module based on MLA212 to be an active line array loudspeaker.

MLA212是一款大型、设计结构精巧的线性阵列扬声器系统，它具有极大的动态容量，吊挂系统采用铝合金材质，安装快捷及保证安全。2只12"强磁大功率低音单元，2只1.4"喉口75芯强磁高音驱动器，箱体采用多层复合夹板，聚脲喷涂。MLA212DA是在MLA212的基础上配置FA2.38功放组件成为有源音箱。



CONFIGURATION



FEATURES

- High quality plywood with polyurea waterproof paint
- High quality neodymium components
- Patent line array horn
- Small cabinet with light weight, but with high SPL
- Passive or Bi-amp operation
- Convenient for hanging and stacking
- Good used for big moving performance, big scale theater, stadium and odeums.

系统特征

- 高质量单元配置，专业线性号角：音质优美，投射精确
- 方便简捷的吊挂方式：安装简易快捷
- 超长品质保证期：品质与信心的保证

适用范围

- 体育场馆、大型演出系统
- 剧院、音乐厅、演艺中心

MODEL

FREQUENCY RESPONSE(-3dB)
DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

MLA212

50Hz-18KHz

2x12"(300mm)/3"voice coil LF

2x1.4"(36mm)/3"voice coil HF

800W(RMS),3200W peak

101dB 1watt/1meter

130dB continuous,136dB peak

8 ohms nominal

Horizontal coverage:100°,

Vertical coverage:varies,depending on

arry length and configuration

400Hz,1.3kHz passive

2×Speakon NL4

570mmx480mmx1055mm

41 kg/pc

47 kg/pc

MLA212DA

50Hz-18KHz

2x12"(300mm)/3"voice coil LF

2x1.4"(36mm)/3"voice coil HF

300W+800W(RMS)

--

130dB continuous,136dB peak

--

Horizontal coverage:100°,

Vertical coverage:varies,depending on

arry length and configuration

--

INPUT TYPE:Balanced Differential line

570mmx480mmx1055mm

43 kg/pc

49 kg/pc