

LHseries LH215

Two-way Loudspeaker System

FEATURES

- High quality plywood with special environmental protection paint
- Very high SPL from a full range passive enclosure
- Fiberglass 90°×50° horn
- Dedicated low distortion mid-bass driver
- Used for moving performance, multipurpose hall and high-end hotel

产品特征

- ●高质量单元配置,高强度夹板箱体
- ●高功率输出,重量轻便于搬运和固定安装
- ●多吊挂点与支撑配合,操作简易快捷
- ●超长品质保证期:品质与信心的保证


适用范围


- ●用于全音域室内、外扩声
- ●多功能厅、高级酒店会所

The LH215 is the ideal general-purpose 2-way loudspeaker with a wide frequency response, suitable for all kinds of mid-field theatre and live venue applications that require professional sound quality, fitted with two 15" neodymium woofers and one 2" exit neodymium compression driver coupled to a special design horn.

LH215是一款双15"两分音全音域音箱。采用两只15"强磁高功率低音单元,一只 2"喉口75芯钛膜高音驱动器配置专门设计的号角,箱体采用多层复合夹板,特殊环保喷涂制作。

CONFIGURATION





FREQUENCY RESPONSE(-3dB) 45 Hz-18kHz

DRIVERS 2×15"(385mm)/4"voice coil LF

 1×2 "(50mm)/3"voice coil HF

RATED POWER 1200W RMS,4800W peak
SENSITIVITY 101dB 1watt/1 metre

MAXIMUM SPL 131dB continuous,137 dB peak

IMPEDANCE 4 ohms nominal

DISPERSION(-6dB) 90°×50°

CROSSOVER FREQUENCIES 1.5 kHz passive INPUT CONNECTORS 2×Speakon NL4

PACKAGE SIZE 660mm×605mm×1250mm

NET WEIGHT 50 kg/pc GROSS WEIGHT 56 kg/pc

