



FT series FT15II

Two-way Loudspeaker System

FEATURES

- High quality MDF with special environmental protection paint
- Wide-bandwidth system
- Rotatable $80^{\circ} \times 50^{\circ}$ horn

The FT15 II is a 2-way system with one 15"(385mm) woofer and one 1"(25mm) exit compression driver mounted on a rotatable $80^{\circ} \times 50^{\circ}$ horn.

FT15 II 是一款15"两分音全音域音箱。采用一只15"高效率低音单元，一只1"喉口34芯钛膜高音驱动器配置 $80^{\circ} \times 50^{\circ}$ 可旋转号角，箱体采用高密度复合板，水性环保喷涂制作。



产品特征

- 优化单元配置，高强度复合板箱体，性价比极高
- 多吊挂点与支撑配合，操作简易快捷
- 超长品质保证期：品质与信心的保证

适用范围

- 用于全音域扩声、语言会议系统
- 多功能厅、高级酒店会所、学校教室
- 小型室外扩声

CONFIGURATION



FREQUENCY RESPONSE(-3dB)	40Hz-20kHz
DRIVERS	1× 15"(385mm)/2.5" voice coil LF 1× 1"(25mm)/ 1.4"voice coil HF
RATED POWER	300W RMS,1200W peak
SENSITIVITY	97dB 1watt/1 metre
MAXIMUM SPL	121 dB continuous,127 dB peak
IMPEDANCE	8 ohms nominal
DISPERSION(-6dB)	$80^{\circ} \times 50^{\circ}$
CROSSOVER FREQUENCIES	2kHz passive
INPUT CONNECTORS	2× Speakon NL4
PACKAGE SIZE	565mm× 545mm× 795mm
NET WEIGHT	27 kg/pc
GROSS WEIGHT	30 kg/pc