

HA series

HA 系列专业功率放大器

HA SERIES PROFESSIONAL AMPLIFIER



pro audio

HA系列专业功放采用标准模块式设计技术，注重产品在长期连续满功率使用条件下的稳定性，该系列产品功率从**300W-1300W**，通道从**2-4**通道任意组合，以适应多种需求。HA系列的产品具有较高阻尼系数和完善滤波系统，使高频更细腻柔和，低频更富有弹性，多通道设计使用更方便。

The HA series professional amplifier using standard modular design techniques, focusing on the stability of the products in the long-term continuous full power conditions, the series power from 300W-1300W, channels from any combination of 2-4 channels to accommodate together a variety of needs. The HA series with higher damping and perfect filtering system, so that the high frequency is more delicate and soft, low-frequency is more flexible. And multi-channel design is more convenient to use.



SPECIFICATIONS

型号: MODEL	HA602	HA802	HA1002	HA1202	HA5803
输出功率 (EIA 1KHZ 1% THD)					
立体声:STEREO POWER 8 ohms	2×600W	2×800W	2×1000W	2×1200W	2×500W+800W
立体声:STEREO POWER 4 ohms	2×900W	2×1400W	2×1750W	2×2000W	2×750W+1200W
桥接:BRIDGE POWER 8 ohms	1800W	2800W	3500W	4000W	1500W+800W
频响: FREQUENCY RESPONSE	20Hz-20kHz, ±1.5dB				
输入灵敏度: INPUT SENSITIVITY	0.775V				0.775V/1.4V/26
信噪比: SIGNAL TO NOISE	> 100dB				
失真度: THD	≤0.05%				
分离度:(8 ohm 1KHz) CROSSTALK	20KΩ (平衡/BALANCED) / 10KΩ (非平衡/UN-BALANCED)				
阻尼系数: (5Hz-1KHz) DAMPING FACTOR	> 230				> 200
转换速率: SLEW RATE	15V/μs				
保护功能: PROTECTION FUNCTION	软启动保护/过热保护/过流保护/直流保护/射频保护 SOFT START / OVERHEATING / OVERCURRENT / DIRECT CURRENT / RADIO FREQUENCY				
电源: MAIN POWER SUPPLY	AC:220-230V 50Hz				
产品尺寸: (W×D×H)mm DIMENSIONS	482×362×88				482×486×88
净重: NET WEIGHT	12.6Kg	14.1Kg	16.3Kg	18.1Kg	21.9Kg