



MLA118W

MLAseries MLA118WASII

Line Array System

FEATURES

- High quality plywood with polyurea waterproof paint
- Direct radiating design
- High temperature 4" (100mm) voice coil

The **MLA118W** is a single 18" low frequency enclosure designed for sub-bass reinforcement to MLA112, made of high quality plywood with polyurea waterproof paint. All rigging parts are made of aluminum alloy. The **MLA118WASII** is equipped with SA2.68II digital amplifier module based on MLA118W to be an active system to push 2pcs MLA112.

MLA118W是一款单18"超低音箱。采用一只18" 100芯低音单元，直射式结构设计，吊挂系统采用铝合金材质，与MLA110或MLA112配合，可吊挂、可堆码，以提升系统低频表现，箱体采用多层复合夹板，聚脲喷涂。MLA118WASII是在MLA118W的基础上配置SA2.68II功放组件成为有源系统，与MLA110或MLA112配合使用。





系统特征

- 高质量单元配置，高强度夹板箱体
- 直射式设计，低音丰富自然
- 超长品质保证期：品质与信心的保证

适用范围

- 配合MLA110或MLA112线性阵列系统，增加低音表现
- 多功能厅、高级酒店会所
- 流动商演、乐队扩声

CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

MLA118W

35Hz-300Hz

1×18"(460mm)/4"voice coil LF

600W RMS,2400W peak

99dB 1watt/1meter

127dB continuous,133dB peak

8 ohms nominal

2×Speakon NL4

965mm×635mm×595mm

43 kg/pc

48 kg/pc

MLA118WASII

35Hz-300Hz and 50Hz-20kHz

1×18"(460mm)/4"voice coil LF

900W/4Ω+1200W/4Ω

--

127dB continuous,133dB peak

--

INPUT TYPE:Balanced Differential line

965mm×635mm×595mm

45 kg/pc

50 kg/pc