

MT-9000

MT-9000系列演出话筒 MT-9000 SERIES PERFORMANCE MICROPHONE

MT-9000是一款U段一拖二真分集无线麦克风系统，双天线自动分级选讯，接收距离远，不易掉线；数字导频，具有数字ID身份识别功能，杜绝干扰和窜频现象；内置强大的音频处理器，相位补偿，失真修正、动态补偿、动态扩展等功能，可根据演出现场灵活选用手持、头戴、领夹麦克风，以满足各种演出场所需要。

MT-9000 is a u-segment one tow two true diversity wireless microphone system, dual antenna automatic grading, receiving far distance, not easy to drop the line; digital pilot, with digital ID identification function, eliminate interference and frequency channeling phenomenon; Built-in powerful audio processor, phase compensation, distortion correction, dynamic compensation, dynamic expansion, etc, according to the performance site flexible selection of handheld, headworn, clip microphone, to meet the needs of various venues.



pro audio

SPECIFICATIONS

	型号MODEL	MT-9000
接收机 RECEIVER	频率范围FREQUENCY RESPONSE	645.25-685.05MHz
	最大通道数 MAX. CHANNELS	200
	带宽 BAND WIDTH	40MHz
	接收灵敏度RECIVER SENSITIVITY	-105dBu
	信噪比 S/N RATIO	≥ 105dB(A计权)
	失真度DISTROTION	< 1%
	音频最大输出电平 MAX. OUTPUT LEVEL	8dBu
	电源POWER	18V DC 800mA
手持麦克风 HANDHELD MICROPHONE	频率范围FREQUENCY RESPONSE	645.25-685.05MHz
	带宽 BAND WIDTH	40MHz
	谐波抑制HARMONIC SUPPRESSION	> 55dBc
	最大频率偏移MAX.FREQUENCY OFFSET	± 48KHz
	频率响应FREQUENCY RESPONSE	50Hz-16KHz(-3dB)
	唛头 CAPSULE	动圈心形 DYNAMIC CARDIOID
	信噪比S/N RATIO	≥ 105dB(A计权)
	失真度THD	< 1%
	电源POWER REQUIREMENTS	2节AA电池或者充电电池 2 AA OR RECHARGEABLE BATTERY
电池寿命BATTERY LIFE	8小时 (碱性电池) 8 HOURS (ALKALINE)	
腰包发射器 BELTPACK TRANSMITTER	频率范围FREQUENCY RESPONSE	645.25-685.05MHz
	带宽BANDWIDTH	40MHz
	谐波抑制HARMONIC SUPPRESSION	> 55dBc
	最大频率偏移MAX.FREQUENCY OFFSET	± 48KHz
	频率响应FREQUENCY RESPONSE	50Hz-18KHz(-3dB)
	话筒MICROPHONE	头戴/领夹迷你XLR, HEADWORN / CLIP MICROPHONE MINI XLR
	信噪比S/N RATIO	≥ 105dB(A计权)
	失真度DISTROTION	< 1%
	电源 POWER REQUIREMENTS	2节AA电池或者充电电池, 2 AA OR RECHARGEABLE BATTERY
电池寿命BATTERY LIFE	8小时 (碱性电池) 8 HOURS (ALKALINE)	