

oro audio



DLAseries DLA112

Line Array System

FEATURES

- High quality plywood with wear-resistant and waterproof polyurea paint
- High quality neodymium components
- Special line array horn
- Small cabinet , light weight, high SPL
- Convenient for supporting, hanging and stacking
- Good used for moving perforamace, small scale theater, stadiums and odeums.

系统特征

- ●高品质单元配置,专用线性号角:保证音 质,投射精准
- ●多种组合使用方式:可吊挂、堆码、支撑, 安装快捷


适用范围


- ●多功能厅、高级会所、会议室、报告厅
- ●流动演出、体育场馆扩声

DLA112 is a medium sized line array speaker with accurate coverage angle, light weight and high SPL. It uses low distortion mid-bass unit, high quality HF driver with special waveguide and horn, accurate and uniform coverage over the effective frequency range. The whole hanging system adopts aluminum alloy material, humanized design makes the system fast installation and ensures safety, and can be used in combination with multiple speakers. Unit configuration: 1x12" high efficiency mid-bass units, 2x1" exit throat 44mm voice coil HF drivers. The wood box adopts multilayer composite plywood, wear-resistant and waterproof polyurea paint.

DLA112是一款中型、覆盖角度精准的线性阵列音箱,它具有比较小的体积和较 轻重量,较大的声压级,应用低失真中低音单元,高品质驱动器配上专用线性 号角,在有效频率范围内,覆盖精确和均匀,吊挂系统采用铝合金材质,安装 快捷并保证安全。1只12"高效率中低音单元,2只1"喉口44芯高音驱动器;箱体 采用多层复合夹板, 耐磨聚脲喷涂。

CONFIGURATION





MODEL FREQUENCY RESPONSE(-3dB) FREQUENCY RESPONSE(-10dB) **DRIVERS**

RATED POWER SENSITIVITY MAXIMUM SPL IMPEDANCE DISPERSION(-6dB)

CROSSOVER FREQUENCIES INPUT CONNECTORS PACKAGE SIZE NET WEIGHT GROSS WEIGHT

DLA112 60Hz-18KHz 55Hz-20kHz

 1×12 "(300mm)/3"voice coil LF 2×1"(25mm)/1.7"voice coil HF 400W RMS,1600W peak 98dB 1watt/1meter 122dB continuous,128dB peak

