



MC-102



MC-104

MC-102/MC-104

无线全数字会议系统 WIRELESS ALL-DIGITAL CONFERENCE SYSTEM

MC-102、MC-104分别是一款一拖二、一拖四无线会议系统。采用UHF超高频段传输，DPLL数字锁相环多信道频率合成技术，使传输更可靠，抗干扰能力更强。方便多套机器同时使用，轻松避开各类干扰。本系统操作简便，安装方便，经济适用，是会议工程的好选择。

MC-102, MC-104 is a one-to-two, one-to-four wireless conference system. It adopts UHF high frequency band transmission and DPLL digital phase-locked loop multi-channel frequency synthesis technology to make transmission more reliable and anti-interference ability stronger. Convenient to use multiple sets of machines at the same time, easily avoid all kinds of interference. The system is easy to operate, easy to install, economic and applicable, is a good choice for conference engineering.

SPECIFICATIONS

型号MODEL	MC-102	MC-104	
接收机 RECEIVER	频率范围Frequency Range	UHF 640-690MHz	UHF 640-690MHz
	调制方式Modulation Mode	FM	FM
	带宽Bandwidth	50MHz	50MHz
	最大通道数Maximum Number of Channels	200	200
	频道间隔Channel Spacing	250KHz	250KHz
	频率稳定度Frequency Stability	± 0.005%以内Range	± 0.005%以内Range
	最大频偏Maximum Frequency Offset	± 45KHz	± 45KHz
	动态范围Dynamic Range	100dB	100dB
	信噪比S/N Ratio	> 105dB	> 105dB
	失真度 THD	≤ 0.5%	≤ 0.5%
	灵敏度Sensitivity	12dB μ V(80dBS/N)	12dB μ V(80dBS/N)
	杂散抑制Spurious Suppression	≥ 75dB	≥ 75dB
	天线接口Antenna Interface	BNC/50 Ω	BNC/50 Ω
	最大输出电平Maximum Output Level	+10dBV	+10dBV
	电源供应Power Supply	DC 13.5V 600mA	DC 13.5V 600mA
	产品尺寸Dimensions	420x190x45mm	420x190x45mm
净重Net Weight	1.7KG	1.8KG	
发射机 TRANSMITTER	载波频率Carrier Frequency	UHF 640-690MHz	UHF 640-690MHz
	音头类型Head Type	电容式Capacitive	电容式Capacitive
	极性模式Polar Mode	单一指向性Single directivity	单一指向性Single directivity
	动态范围Dynamic Range	≥ 100dB	≥ 100dB
	频率响应Frequency Response	40Hz~20KHz	40Hz~20KHz
电源供应Power Supply	DC 3V(1.5V AAx2)	DC 3V(1.5V AAx2)	