

MLA series MLA206



Line Array System



The **MLA206** is a **mini line array loudspeaker** for small and medium scale sound reinforcement, fitted with two 6" LF neodymium drivers and one 1" neodymium HF driver coupled to a patent line array horn, made of high quality plywood with polyurea waterproof paint. All rigging parts are made of aluminium alloy.

MLA206是一款小型、高精度线性阵列扬声器系统，它具有较小的体积和较轻重量，却有较大的声压级，应用低失真中低音单元及高音驱动器加载专利线性号角，能真实还原规定频率范围内音频信号。吊挂系统全部采用铝合金材质，安装简单、快捷及保证安全。单元配置：两只6"高效率强磁中低音单元，一只1"喉口44芯强磁高音驱动器，一只专利声透镜号角；箱体采用多层复合夹板，聚脲喷涂制作。

CONFIGURATION



MODEL
FREQUENCY RESPONSE(-3dB)
FREQUENCY RESPONSE(-10dB)
DRIVERS

RATED POWER
SENSITIVITY
MAXIMUM SPL
IMPEDANCE
DISPERSION(-6dB)

CROSSOVER FREQUENCIES
INPUT CONNECTORS
PACKAGE SIZE
NET WEIGHT
GROSS WEIGHT

FEATURES

- High quality plywood with polyurea waterproof paint
- High quality neodymium components
- Patent line array horn
- Small cabinet with light weight, but with high SPL
- Convenient for hanging and stacking
- Good used for moving performance, small scale theater and band

产品特点

- 高质量单元配置，专利线性号角：高保真音质，投射精确
- 方便简捷的吊挂方式：可吊挂，可堆码，安装快捷、灵活
- 超长品质保证期：品质与信心的保证

适用范围

- 中小型流动演出
- 多功能厅、高级酒店会所

MLA206
90Hz-18kHz
85Hz-20kHz
2×6"(150mm)/1.5"voice coil LF
1×1"(25mm)/1.7"voice coil HF
160W RMS,640W peak
96dB 1watt/1 metre
118 dB continuous,124 dB peak
16 ohms nominal
Horizontal coverage:110°
Vertical coverage:Varies, depending on array length andconfiguration
1.9kHz passive
2×Speakon NL4
412mm×270mm×565mm
9 kg/pc
11 kg/pc