



# CXseries CX10 CX10A

## Two-way Loudspeaker System

The **CX10** is a two-way structure plastic cabinet system with waterproof and sunscreening housing. Fitted with one 10" woofer and one 1"(25mm)exit compression driver coupled to a 90°×60 ° horn.

CX10是一款10寸两分音全音域工程塑胶音箱。采用一只10寸高效率低音单元，一只1寸喇叭25芯高分子聚酯膜高音驱动器，箱体采用工程塑胶注塑而成。CX10A是在CX10的基础上配置150W模拟功放组件成为有源音箱。

### FEATURES

- Strong plastic cabinet
- Molded-in 90°×60 ° horn
- High power output
- Structure plastic cabinet, waterproof and sunscreening





### 产品特征

- 高质量单元配置,工程塑胶箱体,适合全天候使用
- 多吊挂点与支撑配合,可以固定安装与流动使用
- 超长品质保证期: 品质与信心的保证

### 适用范围

- 用于全音域扩声、语言会议系统
- 多功能厅、学校教室

### CONFIGURATION



#### MODEL

#### FREQUENCY RESPONSE(-3dB)

#### FREQUENCY RESPONSE(-10dB)

#### DRIVERS

#### RATED POWER

#### SENSITIVITY

#### MAXIMUM SPL

#### IMPEDANCE

#### DISPERSION(-6dB)

#### CROSSOVER FREQUENCIES

#### INPUT CONNECTORS

#### PACKAGE SIZE

#### NET WEIGHT

#### GROSS WEIGHT

#### CX10

55Hz-20kHz

50Hz-20kHz

1×10"(250mm)/2" voice coil LF

1×1"(25mm)/ 1"voice coil HF

150W RMS,600W peak

95dB 1watt/1 metre

117 dB continuous,123 dB peak

8 ohms nominal

90°×60°

2.5 kHz passive

2×Speakon NL4

405mmx325mmx565mm

10 kg /pc

12 kg/pc

#### CX10A

55Hz-20kHz

50Hz-20kHz

1×10"(250mm)/2" voice coil LF

1×1"(25mm)/ 1"voice coil HF

150W RMS

/

117 dB continuous,123 dB peak

Line 20k ohm Mic: 2k ohm

90°×60°

/

/

405mmx325mmx565mm

13 kg /pc

15 kg/pc