



pro audio



ES series ES104

Two-way Loudspeaker System

The **ES104** is a highly weather-resistant, single 4" 2-way full range outdoor loudspeaker, the body is made of engineering plastic injection molding. fitted with one 4" mid-woofer and one 0.8" dome tweeter. The system conforms to IP65 international standard. ES104T is equipped with multi-tap transformer based on ES104.

ES104是一款4"两分音系列音箱。箱体设计优先考虑全天候使用环境，采用工程塑胶注塑而成，一只4寸中低音单元和一只20芯球顶高音配置。带T的产品配置多种输出功率选择功能的定压音箱。产品符合IP65国际标准。

FEATURES

- Highly weather-resistant IP65 rating
- Engineering plastic injection molding
- Two kinds of mounting brackets
- Good used for meeting rooms, shops, water parks, outdoor background music, swimming pools, and a wide variety of other outdoor or indoor background music




产品特点

- 采用工程塑胶注塑而成

适用范围

- 用于分散扩声
- 会议室
- 主题公园、景区扩声

CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

INPUT VOLTAGE

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

ES104B/ES104W

75Hz-20kHz

70Hz-20kHz

1×4"(100mm)/1"voice coil LF

1×0.8"(20mm)/dome tweeter

40W RMS,160W peak

88dB 1watt/1 metre

104dB continuous,110dB peak

16 ohms nominal

120°×90°

3.5kHz passive

covered barrier strip terminals

414mm×190mm×285mm(1Pair)

2 kg/pc

6 kg/pair

ES104BT/ES104WT

75Hz-20kHz

70Hz-20kHz

1×4"(100mm)/1"voice coil LF

1×0.8"(20mm)/dome tweeter

100V

10W/20W/40W/OFF/16Ω

88dB 1watt/1 metre

104dB continuous,110dB peak

16 ohms nominal

120°×90°

3.5kHz passive

covered barrier strip terminals

414mm×190mm×285mm(1Pair)

3 kg/pc

7 kg/pair