



pro audio



MRseries MR15CNA

Two-way Loudspeaker System

FEATURES

- High quality plywood with polyurea waterproof paint
- Neodymium HF driver and LF driver
- Patent 70° x 40° horn

The MR15CN is a high precision and high power stage monitor, made of high quality plywood with polyurea paint. It offers a "studio monitoring" type of response, exceptional dynamic capability and very low distortion. Fitted with one 15" neodymium woofer and one 1" exit neodymium compression driver coupled to a patent 70° x 40° horn. MR15CNA is equipped with FA1.6 digital amplifier module based on MR15CN to be an active monitor.

MR15CN是一款15寸同轴两分音全音域舞台监听音箱，采用一只15寸高效率强磁中低音单元和一只1寸喉口44芯强磁驱动器，配置专门设计的70° x 40°号角。箱体采用多层复合夹板，聚脲喷涂制作。MR15CNA是在MR15CN的基础上配置FA1.6功放组件成为有源音箱。

产品特征



- 高质量单元配置，高强度夹板箱体
- 超长品质保证期：品质与信心的保证

适用范围

- 多功能厅、高级酒店会所
- 流动商演、乐队扩声以及舞台返送音箱



CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

MR15CN

70Hz-18kHz

65Hz-20kHz

1×15"(385mm)/3"voice coil LF

1×1"(25mm)/1.7"voice coil HF

400W RMS,1600W peak

97dB 1watt/1 metre

124dB continuous,130dB peak

8 ohms nominal

70° × 40°

2.2kHz passive

2×Speakon NL4

590mm×440mm×635mm

20 kg/pc

24 kg/pc

MR15CNA

70Hz-18KHz

65Hz-20kHz

1×15"(385mm)/3"voice coil LF

1×1"(25mm) / 1.7"voice coil HF

600W/8Ω

--

124dB continuous,130dB peak

--

70° × 40°

--

INPUT TYPE: Balanced Differential line

590mm×440mm×635mm

22 kg/pc

26 kg/pc