



# M series

## M 系列调音台 M SERIES MIXER

M8/M12/M16是三款多功能模拟调音台，具有体积小、重量轻、功能全、操作直观、音色自然等特点。内置模拟效果器，自带蓝牙、USB播放功能，USB录音功能。适合中小型演出、会议室、文化礼堂、多功能厅等各种扩声系统。

The M8/ M12/ M16 is a multi-functional analog mixer with features of small size, light weight, full function, intuitive operation and natural sound. Built-in simulation effect, with Bluetooth, USB playback function, USB recording function. Suitable for small and medium-sized performances, conference rooms, cultural halls, multi-function halls and other sound reinforcement system.

### SPECIFICATIONS

型号MODEL	M8	M12	M16
麦克风输入Micphone Input	4路 4 channels	8路 8 channels	12路 12 channels
立体声输入Stereo Input	4路 4 channels	4路 4 channels	4路 4 channels
USB/蓝牙输入USB/Bluetooth Input	2路 2 channels	2路 2 channels	2路 2 channels
立体声主输出Stereo Main Output	2路 2 channels	2路 2 channels	2路 2 channels
编组输出Marshalling Output	2路 2 channels	2路 2 channels	2路 2 channels
辅助输出Secondary Output	1路 1 channel	1路 1 channel	1路 1 channel
监听输出Monitor Output	1路 1 channel	1路 1 channel	1路 1 channel
频率响应Frequency Response	20Hz-20KHz ± 0.5dB	20Hz-20KHz ± 0.5dB	20Hz-20KHz ± 0.5dB
总谐波失真 THD	≤ 1%(额定条件Rating Conditions:20Hz-20KHz)		
等效输入噪音 Equivalent Input Noise	≤ -110dBm	≤ -110dBm	≤ -110dBm
输入通道EQ特性 Input Channel EQ	低频LF:80Hz ± 15dB;中频MF:2.5KHz ± 15dB;高频HF:12KHz ± 15dB;		
线路输入最大增益 Line Input Max Gain	≥ 20dB	≥ 40dB	≥ 40dB
话筒输入最大增益 Microphone Input Max Gain	≥ 50dB	≥ 60dB	≥ 60dB
输入阻抗 Input Impedance	话筒Microphone: ≥ 1.0KHz;线路Circuit: ≥ 10KHz; 辅助返回输入Auxiliary Returnst:20KHz		
输出阻抗 Output Impedance	主总输出Master Total : ≤ 300 Ω ;录音输出Audiot: ≤ 10KHz;辅助输出Secondary : ≤ 10KHz		
效果器Effectors	模拟效果器,延时时间/重复次数可调 Emulator With Adjustable Delay Time/Repetition		
工作电压Operating Voltage	AC 220V/50Hz	AC 220V/50Hz	AC 220V/50Hz
整机功耗Power Consumption	≤ 40W	≤ 40W	≤ 40W
产品尺寸Dimensions ( HxWxD ) mm	95x345x410	90x445x410	90x500x410
净重NET Weight	3.84 KG	5.1 KG	5.7 KG